

AIR FLOW AND VELOCITY TRANSMITTERS DPT-FLOW

Multifunctional air flow transmitters for building automation systems

The DPT-Flow series air flow transmitters are engineered for building automation in the HVAC/R industry. The most technologically advanced transmitters on the market, measuring volume flow, velocity, and static and differential pressure. The DPT-Flow series devices can be connected directly to the pressure measurement points in a centrifugal fan, providing accurate flow measurement of the fan. The smart user interface enables easy selection of settings according to the selected fan or in-duct measurement probe.



DPT-Flow series devices include:

- Two field selectable functions:
 - o Measure and monitor in-duct volume flow, velocity or differential pressure
 - o Measure and monitor air flow across centrifugal fans
- Multiple field selectable measurement units:
 - o Volume flow: m³/s, m³/h, cfm, l/s
 - o Velocity: m/s, ft/min
 - o Pressure: Pa, inWC, mmWC, kPa, mbar
- Unique proportional output options:
 - o Volume flow or velocity: voltage (0–10 V) or current (4–20 mA)
 - o Pressure: voltage (0–10 V) or current (4–20 mA)



DPT-Flow series device options offer:

- AZ (autozero) function for automatic zero point calibration, eliminating the need for periodic manual autozeroing to ensure long term accuracy

SIMILAR PRODUCTS

- AVT series air velocity transmitters
- DPT-2W-Q series differential pressure transmitters with flow linear output
- DPT-R8 series 8-range differential pressure transmitters
- DPT-MOD series differential pressure transmitters with Modbus configuration

APPLICATIONS

DPT-Flow series devices are commonly used in HVAC/R systems for:

- air flow monitoring across centrifugal fans and blowers
- in-duct air flow monitoring
- VAV applications

MODEL SUMMARY

	DPT-FLOW-1000		DPT-FLOW-2000		DPT-FLOW-5000		DPT-FLOW-7000	
Measurement ranges (Pa)	0–1000 Pa		0–2000 Pa		0–5000 Pa		0–7000 Pa	
Description	Model	Product code	Model	Product code	Model	Product code	Model	Product code
Flow meter for measuring air flow in duct and on centrifugal fans								
- with display	DPT-FLOW-1000-D	102.001.012	DPT-FLOW-2000-D	102.002.009	DPT-FLOW-5000-D	100.004.012	DPT-FLOW-7000-D	102.006.013
- with autozero and display	DPT-FLOW-1000-AZ-D	102.001.002	DPT-FLOW-2000-AZ-D	102.002.002	DPT-FLOW-5000-AZ-D	102.004.003	DPT-FLOW-7000-AZ-D	102.006.002

AIR FLOW AND VELOCITY TRANSMITTERS

DPT-FLOW

Multifunctional air flow transmitters for building automation systems

SPECIFICATIONS

Performance

Accuracy (at applied pressure):

Ranges < 125 Pa = ±2 Pa

Ranges 125 Pa = ±1,5 % Pa

(Accuracy specifications include: general accuracy, temperature drift, linearity, hysteresis, long term stability, and repetition error)

Thermal effects:

Temperature compensated across the full spectrum of capability

Overpressure:

Proof pressure: 25 kPa

Zero point calibration:

Automatic autozero or manual pushbutton

Response time:

1.0–20 s, selectable via menu

Technical Specifications

Media compatibility:

Dry air or non-aggressive gases

Pressure units (select via menu):

Pa, kPa, mbar, inWC, mmWC

Pressure output scale (select via menu):

	DPT-Flow-1000	DPT-Flow-2000	DPT-Flow-5000	DPT-Flow-7000
Pa	100-1,000	200-2,000	500-5,000	700-7,000
kPa	0.1-1.0	0.2-2.0	0.5-5.0	0.7-7.0
mbar	1-10	2.0-20	5.0-50	7.0-70
mmWC	10-100	20-200	50-500	70-700
inWC	0.4-4.0	0.8-8.0	2.0-20	2.5-30

Flow units (select via menu):

Volume: m³/s, m³/hr, cfm, l/s

Velocity: m/s, ft/min

Flow output scale (select via menu):

Units	Range
m ³ /s	0.025-50
m ³ /hr	100-200,000
cfm	50-100,000
l/s	25-50,000
m/s	1-100
ft/min	200-20,000

Measuring element:

MEMS

Environment:

Operating temperature:

-10...50 °C

with autozero (-AZ) calibration -5...50 °C

Storage temperature:

-20...70 °C

Humidity:

0 to 95 % rH, non condensing

Physical

Dimensions:

Case: 90.0 x 95.0 x 36.0 mm

Weight:

150 g

Mounting:

2 each 4.3 mm screw holes, one slotted

Materials:

Case: ABS

Lid: PC

Duct connectors: ABS

Tubing: PVC

Protection standard:

IP54

Display

2-line display (12 characters/line)

Line 1: Volume or velocity measurement

Line 2: Pressure measurement

Size: 46.0 x 14.5 mm

Electrical connections:

4-screw terminal block

Wire: 12–24 AWG (0.2–1.5 mm²)

Cable entry:

Strain relief: M16

Knockout : 16 mm

Pressure fittings

Male Ø 5.0 mm and 6.3 mm

Electrical

Voltage:

Circuit: 3-wire (V Out, 24 V, GND)

Input: 24 VAC or VDC, ±10 %

Output: 0–10 V, selectable via jumper

Power consumption: <1.0 W

Resistance minimum: 1 kΩ

Current:

Circuit: 3-wire (mA Out, 24 V, GND)

Input: 24 VAC or VDC, ±10 %

Output: 4–20 mA, selectable via jumper

Power consumption: <1.2 W

Maximum load: 500 Ω

Conformance

Meets requirements for CE marking:

EMC Directive 2014/30/EU

RoHS Directive 2002/95/EY



AZ-calibration is a function in the form of an automatic zeroing circuit built into the PCB board. The AZ-calibration electronically adjusts the transmitter zero at predetermined time intervals (every 10 minutes). The AZ-calibration eliminates all output signal drift due to thermal, electronic or mechanical effects, as well as the need for technicians to remove high and low pressure tubes when performing initial or periodic transmitter zero point calibration.

The AZ adjustment takes 4 seconds. To avoid conflict with the BAS system, the output and display values will freeze to the latest measured value, after which the device returns to its normal measuring mode. Transmitters equipped with the AZ-calibration are virtually maintenance free.

How to generate a model?

Example:	Product series			
DPT-FLOW-1000-AZ-D	DPT-FLOW	Air flow transmitter		
		Highest available measurement range		
		-1000	0...1000 Pa	
		-2000	0...2000 Pa	
		-5000	0...5000 Pa	
		-7000	0...7000 Pa	
		Zero Point Calibration		
		-AZ	With autozero calibration	
			Standard with pushbutton manual auto zero	
		Display		
		-D	With display	
			Without display	
Model	DPT-FLOW	-1000	-AZ	-D